



ULC Listed

Electrical Specifications:

(FOR 60" O.D. TANK)

- Max. Switching Voltage (VOLTS DC/AC): 240
- Max. Switching Current (AMPS DC/AC): 1.0
- Max. Switching Power (WATTS DC/AC): 100
- Max. Operating Temperature: 90°C (194°F)

Meets Standards;
 Class 1, Division 1, Groups B,C,D
 CSA 22.2 No. 1010-1 & ANSI/I SA S82-03
 CSA 22.2 No. 30 and UL 1203

Construction:

- 316 SS Stem
- 2" Dia. 316 SS Float
- 2" NPT Bushing

This drawing is the exclusive property of STEELCRAFT Inc. and is proprietary and confidential information. This drawing and the information contained therein must not be duplicated, used, divulged, reproduced, copied, disclosed or appropriated in whole or in part for any purpose other than as expressly authorized by STEELCRAFT Inc. This drawing must be returned promptly upon request.

STEELCRAFT

Engineered Products Division

| | | | |
|--|--------------------|------------|--|
| DESCRIPTION: HIGH/LOW LEVEL ALARM SWITCH | | | |
| CUSTOMER: | | | |
| PROJECT: | | | |
| ITEM NO.: | DRN.: HK 4-NOV-15 | SCALE: 1:7 | |
| JOB NO.: | DWG. NO.: 2FLOAT60 | | |